JOORS

USCG DOORS

B CLASS DOOR



SC-B-0-H

B-0 FIRE DOOR

Complies with USCG requirements as defined in 46 CFR 72-05-25, 46 CFR 116.435, and NVIC 9-97 for specific construction features of B-class bulkhead doors for domestic vessels.

FRAME: 1/8" Steel Z Frame

Bolt-In or Clamp-In Application

BLADE: Two Steel 20 gage pans filled with

USCG approved insulation core 1 3/4" or 1 3/8" blade thickness.

Four door edges trimmed with painted or stainless channel.

To be fitted with backing plates top or bottom for attachment of closers

or other hardware.

HARDWARE: Hinges- Stainless Steel GSV


Locksets- Trioving Marine or

Best Access cylindrical

Closer- Option as required

FINISH: Prime Painted or Finish Painted

DOOR



DOUBLE TOP PANEL PANIC BAR VENTILATION KICKOUT PANEL

sales@shipinteriorsystems.com www.shipinteriorsystems.com 541-436-4440



SHIP INTERIOR SYSTEMS, LLC 1767 12th Street #128 Hood River, OR 97031

JOORS

USCG DOORS

B CLASS DOOR



SC-B15-H

4#' 8D76AAD

 $5a_b'[Wei [fZ GE59 dWcg[dW] W fe SeVW[WV [&(58D) $Z'' ZS' + &(58D \##(Z8\% + S' V @H; 5 + Z+) Xad ebWL[X]UUa` efdgUf[a` XWSfgdWeaX4ZL/SeeTg'] ZWSV Vaade XadVa_ V\text{Wf}[UhWebWex]$

FRAME: 1/8" Steel Z Frame

Bolt-In or Clamp-In Application

BLADE: Two Steel 20 gage pans filled with

USCG approved insulation core 1 3/4" or 1 3/8" blade thickness.

Four door edges trimmed with painted or stainless channel.

To be fitted with backing plates

top or bottom for attachment of closers or

other hardware.

HARDWARE: Hinges- Stainless Steel GSV

Locksets- Trioving Marine or

Best Access cylindrical

Closer- Option as required


FINISH: Prime Painted or Finish Painted



VISION




SINGLE



DOUBLE DOOR



TOP PANEL



PANIC BAR



VENTILATION LOUVRE



KICKOUT PANEL

sales@shipinteriorsystems.com www.shipinteriorsystems.com 541-436-4440



SHIP INTERIOR SYSTEMS, LLC 1767 12th Street #128 Hood River, OR 97031